

KAESER
KOMPRESSOREN®



Program MOBILAIR® S CE usklađenošću

Mobilni kompresori sa svjetski priznatim sustavom SIGMA PROFIL 

Količina dobave od 1,2 do 48,1 m³/min

www.kaeser.com

Alternativni pogoni

Alternativni pogoni				e-power	
Model			M 13	M 17	M 13E
Volumni protok pri radnom pretlaku	7 bara	m³/min	1,2	–	1,25
	100 psi	cfm	42		44
	10 bara	m³/min	1,0	–	1,0
	145 psi	cfm	35		35
	13 bara	m³/min	0,85	–	0,85
	175 psi	cfm	30		30
	15 bara	m³/min	–	1,0	0,75
	200 psi	cfm		35	27
Tip motora			Honda GX 630	Honda GX 630	Siemens
Nazivna snaga motora kW			15,5	15,5	7,5
Obrada komprimiranog zraka			○	○	○



Kompaktni uređaji

Kompaktni uređaji						e-power			
Model			M 20	M 27	M 30	M 27E	M 31E	M 50E	
Volumni protok pri radnom pretlaku	7 bara	m³/min	2,0	2,6	2,9	2,6	3,15	5,0	
	100 psi	cfm	71	92	100	92	110	180	
	10 bara	m³/min	–	2,1	–	–	2,6	3,8	
	145 psi	cfm		74			92	135	
	12 bara	m³/min	–	1,9	–	–	2,3	–	
	175 psi	cfm		67			81		
	14 bara	m³/min	–	1,6	–	–	1,9	–	
	200 psi	cfm		57			67		
Tip motora			Kubota D722	Kubota D1105	Kubota D1105	Siemens	Siemens	Siemens	
Nazivna snaga motora			kW	14,7	18,2	18,2	15	22	25
Obrada komprimiranog zraka			○	○	○	○	○	○	
Opcija generator			kVA	–	6,5	–	–	–	




Višenamjenski uređaji

Model			M 58utility	M 59		M 65		M 82
Volumni protok pri radnom pretlaku	7 bara	m³/min	5,1	5,5		6,6		8,4
	100 psi	cfm	180	195		230		295
	10 bara	m³/min	4,35	4,7		5,6		6,8
	145 psi	cfm	155	165		195		240
	12 bara	m³/min	–	–		–		6,1
	175 psi	cfm						215
	14 bara	m³/min	–	3,8		4,6		5,5
	200 psi	cfm		135		160		195
Tip motora			Kubota V2403-CR	Hatz 3H50TICD		Kubota V2403CR-T		Kubota V3307-CR-T
Nazivna snaga motora		kW	35,3	43,5		47,9		54,6
Obrada komprimiranog zraka			○	○		○		○
Opcija generator		kVA	–	8,5 / 13		–		8,5 / 13



Snažni uređaji

Model			M 125		M 171	
Volumni protok pri radnom pretlaku	8,6 bara	m³/min	–		17,0	
	125 psi	cfm			600	
	10 bara	m³/min	11,5		15,5	
	145 psi	cfm	405		550	
	12 bara	m³/min	10,7		13,5	
	175 psi	cfm	380		475	
	14 bara	m³/min	9,7		11,5	
	200 psi	cfm	345		405	
Tip motora			Deutz TCD 4.1 L04		Deutz TCD 6.1 L06	
Nazivna snaga motora		kW	105		129	
Obrada komprimiranog zraka			○		○	
Opcija generator		kVA	13		–	



Veliki kompresori

Volumni protok pri radnom pretlaku					e-power	
Model			M 255		M 250E	M 255E
Volumni protok pri radnom pretlaku	8,6 bara	m³/min	26,5		25,0	–
	125 psi	cfm	950		885	
	10 bara	m³/min	24,8		20,4	24,7
	145 psi	cfm	875		720	875
	12 bara	m³/min	–		–	19,9
	175 psi	cfm				705
	14 bara	m³/min	19,7		16,2	–
	200 psi	cfm	695	570		
Tip motora			Cummins B6,7	Siemens	Siemens	
Nazivna snaga motora kW			210	132	160	
Obrada komprimiranog zraka			○	○	○	

